

# Specifications — IRCM, ACM, RCM, and CM Series

## General

### Power

CM-3BLB, CM-9BLB, CM-19AC

12 VDC from an Extron MLC 226 IP or MLC 104 IP Plus Series MediaLink™ Controller or System 5 IP Switcher  
or from an optional external power supply

### Power input requirements

12 VDC, 0.02 A

All other models ..... 12 VDC from an Extron MediaLink Controller (MLC) or System 5 IP Switcher

### Power input requirements

12 VDC, 0.02 A

Temperature/humidity ..... Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing  
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing

Rack mount ..... Yes, with optional faceplate, and furniture/wall mountable with optional faceplates or AAP wall plates

Enclosure type ..... Metal

### Enclosure dimensions

IRCM-VCR, IRCM-DVD, IRCM-Tape, ACM-Tone, ACM-Level, RCM-SC, RCM-SCLT, CM-5BB, CM-3BLB

Faceplate ..... 1.4" H x 3.5" W x 0.1" D (3.5 cm H x 8.9 cm W x 0.3 cm D) (double space AAP plate)

Boards ..... 1.3" H x 2.6" W x 0.9" D (3.3 cm H x 6.6 cm W x 2.3 cm D)  
(Depth excludes buttons. Allow at least 2.1" (5.3 cm) depth in the wall/furniture.)

IRCM-DVD+, IRCM-DV+, CM-20BB, CM-9BLB, CM-19AC

Faceplate ..... 2.8" H x 3.5" W x 0.1" D (7.1 cm H x 8.9 cm W x 0.3 cm D) (four space AAP plate)

Boards ..... 2.7" H x 2.6" W x 0.9" D (6.9 cm H x 6.6 cm W x 2.3 cm D)  
(Depth excludes buttons. Allow at least 2.1" (5.3 cm) depth in the wall/furniture.)

### Product weight

IRCM-VCR, IRCM-DVD, IRCM-Tape, ACM-Tone, ACM-Level, RCM-SC, RCM-SCLT, CM-5BB, CM-3BLB  
0.1 lbs (<0.1 kg)

IRCM-DVD+, IRCM-DV+, CM-20BB, CM-9BLB, CM-19AC  
0.2 lbs (0.1 kg)

Shipping weight ..... 1 lbs (1 kg)

Vibration ..... ISTA 1A in carton (International Safe Transit Association)

Listings ..... UL, CUL as components of the MLC 206, or MLC 226 IP, or MLC 104 IP Plus Series MediaLink™ Controller; or System 5 IP Switcher

Compliances ..... CE, FCC Class A, VCCI, AS/NZS, ICES as components of the MLC 206, MLC 226 IP, or MLC 104 IP Plus Series MediaLink™ Controller; or System 5 IP Switcher

MTBF ..... 30,000 hours

Warranty ..... 3 years parts and labor

**NOTE** Specifications are subject to change without notice.

(7.52-053007-D4)